Luton Walkway **BXMW/LU-WALK**





Standard Unit Dimensions:

Covered Walkways Specification Shee

Bespoke sizes to suit customer requirements

Framework Colours/Finishes:



The colours shown are a guide only. Please check a colour chart to see the actual colour.

Product Information

The Luton is a light weight yet sturdy walkway, comprising stylish circular uprights and purlins. Available in a Symmetric or Asymmetric design, corners and bends can be easily accommodated using hip joints or individual canopies which overlap. The Luton can also accommodate side panels to form a partially or fully enclosed walkway.

Features

.

- 4mm ClearView PETg UV sheeting
- Base plate or submerged fixing
- Robust, tough construction
- Welded end frames and purlin section made from heavy duty box section
- Assembled with anti-tamper high strength bolts

Materials Used

- Framework Mild steel
- Cladding 16mm structured multi-wall polycarbonate
- Fasteners Zinc plated
- Cover Strips Aluminium capex

Finish Options (Framework)

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com













1

CE EN 1091-1

imensions are in millimeters, weights in kilograms and capacities in litres, are approximate and do not form any part of the contract. All prices are guide prices only and should be used for estimating purposes only. Broxap Limited reserve the right to change the design, specification or price of any item sold at any time All prices exclude VAT and delivery. Please Note: All information on this data sheet is subject to orientation (NS.EW) altitude and proximity to buildings, but is sufficient for use as general/preliminary information).

Luton Walkway **BXMW/LU-WALK**



Fire Resistance

Cladding is fire tested to '1Y' for BS 476

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees* on cladding material(s)
- 10 years' warranty* on material (only)
- 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply

Options

•

.

.

- Side Panels in PETg or Glazed Finish
- Trapezoidal Roof Cladding
- Opal Cladding on the roof and side panels
- Powder Coating to a wide range of colours
- UPVC or Aluminium Guttering
- LED lighting or solar lighting
- Full installation service

Diagram

Installation

Submerged Surface Mounted Baseplate Baseplate

customer requirements Framework Colours/Finishes: RAL 9006 RAL 7016 Galvanised Only White Anthracite Aluminium Grey RAL 9005 RAL 3020 Traffic Red Jet Black BS 4800 00 A 05 RAL 1023 BS 4800 14 C 39 Holly G se Grev RAL 5013 RAL 9016 Mid Blue Dark Blue Traffic White

Standard Unit Dimensions:

Bespoke sizes to suit

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com



The colours shown are a guide only. Please check a colour chart to see the actual colour.











2

CE EN 1091-1

All dimensions are in millimeters, weights in kilog Note: All informat ontract. All pric ices are guide prices only and shou subject to orientation (N.S.E.W) altit Id be used for estimating purposes only. Broxap Limited reserve the right to ude and proximity to buildings, but is sufficient for use as general/oreliminar pecification or price of any item sold at any time in litres, are approximat ude VAT and delivery. Pl to change the deary information).

