Luton Entrance Canopy **BXMW/LUEC**





Standard Unit Dimensions:

Length: 5000mm Width: 3000mm Height: 2300mm

Framework Colours/Finishes:











Traffic White

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Product Information

The Luton is a light weight yet sturdy Entrance Canopy, comprising stylish circular uprights and purlins. This shelter can also accommodate side panels to form a partially enclosed entrance foyer.

Features

- 4mm ClearView PETg UV roof
- Base plate or submerged fixing
- Robust, tough construction
- Welded end frames and purlin sections made from heavy duty box section assembled with anti-tamper high strength bolts
- Hot dipped galvanized

Materials Used

- Framework Mild steel
- Cladding 4mm ClearView PETg UV roof
- Fasteners Zinc plated
- Cover Strips Aluminium capex

Finish Options (Framework)

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com

















Luton Entrance Canopy BXMW/LUEC



Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Fire Resistance

Cladding is fire tested to '1Y' for BS 476

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees* on cladding material(s)
- 10 years' warranty* on material (only)
- 12 months' warranty* on parts & labour

Options

- Bespoke Sizes on Request
- Side Panels in PETg or Glazed Finish
- Metal profile, trapezoidal roof cladding
- Opal Cladding on the roof and side panels
- Powder Coating to a wide range of colours
- **UPVC** or Aluminium Guttering
- Aluminium Profile Weather Resistant Barriers
- Wall Mounting to Rear (Dependant on Suitability of Existing Structure)
- LED Lighting or solar lighting
- Full installation service

Standard Unit Dimensions:


Length: 5000mm Width: 3000mm Height: 2300mm

Framework




The colours shown are a guide only. Please check a colour chart to see the actual colour.

Diagram



Installation



Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com

















^{*}Maintenance and other qualifying criteria apply