**Standard Unit Dimensions:** 

Width: 715mm

Height: 800mm

Diameter: 48.3mm

**Recommended spacing** between cycle stands:

800mm

**Colours/Finishes:** 

RAL 9006

White

Aluminium

RAL 3020

Traffic Red

RAL 1023

Traffic Yellow

RAL 5013

Dark Blue

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Only

14 C 39

Holly Gree

RAL 5015

Mid Blue

RAL 7016

Anthracite

Grey

RAL 9005

BS 4800

00 A 05

Goose Grey

RAL 9016

Traffic White

# Sheffield Cycle Stand **BXMW/GS/Sheffield-Stand**





### **Product Information**

The Sheffield Cycle Stand is recommended by the national cycling associations, this best selling tubular cycle stand allows the bike to be secured in a variety of ways. Simple and easy to install this cycle stand is available in a variety of different sizes, fixings and finishings. Thus allowing this best selling cycle stand to complement any external environment, and pre-existing street furniture suite.

### **Features**

- Hot dipped galvanised to BS EN ISO 1461:2009
- Recommended by the national cycling associations
- Available in a variety of different sizes, fixings and finishings
- Complements any external environment
- Available root fixed or baseplated

## **Materials Used**

Framework - Mild Steel

### **Finish Options**

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated
- Stainless Steel Grade 304 • •
- Stainless Steel Grade 316
- Duracast<sup>™</sup> Polyurethane version •

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com













t form any part of the contract. All prices are guide prices only and should be used for estimating purposes only. Broxap Limited reserve the right to change the design, All information on this data sheet is subject to orientation (N,S,E,W) altitude and proximity to buildings, but is sufficient for use as general/preliminary information). All dimensions are in millimete nensions are in millimeters, weights in kilograms and capacities in litres, are appro specification or price of any item sold at any time. All prices exclude VAT and deliv

Standard Unit Dimensions: Width: 715mm Height: 800mm Diameter: 48.3mm

Recommended spacing between cycle stands: 800mm

**Colours/Finishes:** 

RAL 9006

White Aluminium

RAL 3020

Traffic Red

RAL 1023

Traffic Yellow

RAL 5013

Dark Blue

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Galvanised Only

14 C 39

Holly Green

Mid Blue

RAL 7016

Anthracite

Grey

RAL 9005

BS 4800

00 A 05

Goose Grey

RAL 9016

Traffic White

# Sheffield Cycle Stand BXMW/GS/Sheffield-Stand



#### Guarantees, Warranties, Design-Life and Life-Expectancies


- 25 year structural guarantee\*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' warranty\* on material (only)
- 12 months' warranty\* on parts & labour

\*Maintenance and other qualifying criteria apply

### **Options**

- Stands also available in junior size See Sheffield Junior Cycle Stand for details
- Polyester powder coating to RAL and BS colours
- · Available in a range of different sizes, fixings and finishings

#### Diagram



Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com









CHAS



