Bury Bandstand **BXMW/BURY**





Standard Unit Dimensions:

Bandstands Specification Shee

Across corners: 8115mm Across flats: 7500mm Pitch circle diameter of coloumns: 7000mm Height overall: 6350mm (5400mm excluding finial) Height to underside of eaves: 3200mm

Colours/Finishes:

	RAL 9006	RAL 7016
Galvanised Only	White Aluminium	Anthracite Grey
BS 4800 10 A 07	RAL 3020	RAL 9005
Nimbus Grey	Traffic Red	Jet Black
BS 4800 14 C 39	RAL 1023	BS 4800 00 A 05
Holly Green	Traffic Yellow	Goose Grey
RAL 5015	RAL 5013	RAL 9016
Mid Blue	Dark Blue	Traffic White
The colours shown are a guide only. Please check a colour chart to see the actual colour.		

Product Information

Traditional style bandstand that is produced using modular components allowing a quick and easy installation, utilising lightweight sections to achieve stability whilst maintaining aesthetics.

Features

- Architectural cast aluminium feature columns, eaves beams and ball/finial to top of roof
- Open soffit to expose profiled aluminium roof support structure
- Central roof support adorned with cast aluminium feature finial
- Aluminium roof sheeting
- No guttering

Materials Used

Modular design, utilising lightweight sections to achieve stability whilst maintaining aesthetics

Finish Options

- Hot dip galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com













Standard Unit Dimensions:

Across corners: 8115mm Across flats: 7500mm Pitch circle diameter of coloumns: 7000mm Height overall: 6350mm (5400mm excluding finial) Height to underside of eaves: 3200mm

Colours/Finishes:



Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com



All dimensions are in millimetres, weights in kild





act. All pri





Il prices are guide prices only and should be used for estimating purposes only. Broxap Limited reserve the right t t is subject to orientation (N,S,E,W) altitude and proximity to buildings, but is sufficient for use as general/prelimina





specification or price of any item sold at any time

Fire Resistance

Bury Bandstand

Cladding is fire tested to '1Y' for BS 476


Guarantees, Warranties, Design-Life and Life-Expectancies


- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees* on cladding material(s)
- 10 years' warranty* on material (only)
- 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply

Diagram

Installation





broxap

shelters & canopies