# Thames Bridge Cycle Stand **BXMW/THB**





#### **Standard Unit Dimensions:**

Height: 1400mm Steady Support Height: 580mm Capacity: 1 Cycle

#### **Colours/Finishes:**



Please check a colour chart to see the actual colour.

# **Product Information**

The Thames Bridge Cycle Stand is only available as a single stand. A great space saving solution. *Rack is not included for multiple stands.* 

#### **Features**

- Front wheel mounted at intermediate level
- Steady support at low level
- Locking mechanism to secure bicycle

## **Materials Used**

Framework - Mild Steel

# **Finish Options**

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com

re guide prices only and should be use t to orientation (N,S,E,W) altitude and p





act. All prid





erve the right t neral/prelimina



ation or price of any item sold at any time

Standard Unit Dimensions: Height: 1400mm Steady Support Height: 580mm Capacity: 1 Cycle

Colours/Finishes:

White

Aluminium

RAL 3020

Traffic Red

RAL 1023

RAL 5013

Dark Blue

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Galvanised

Only

BS 480C 10 A 07

BS 4800 14 C 39

Mid Blue

nbus Grey

RAL 7016

Anthracite

Grev

RAL 9005

Jet Black

BS 4800 00 A 05

Goose Grey

RAL 9016

Traffic White

# Thames Bridge Cycle Stand **BXMW/THB**



# Guarantees, Warranties, Design-Life and Life-Expectancies

- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 12 months' warranty\* on parts & labour

\*Maintenance and other qualifying criteria apply

## **Options**

- Available in a range of colours
- Wall mounted or can be rack mounted
- Optional Zinc Rich Primer

## Diagram















