Ascot Bandstand BXMW/ASCOT





Product Information

The Ascot Bandstand is enhancing commercial and corporate facilities at the prestigious racecourse.

This traditional bandstand was originally commissioned by the prestigious racecourse to re-instate an element of Ascot heritage to the recently built modern grandstand.

Features

•

.

•

•

•

- 8 aluminium architectural cast columns
- Aluminium fabricated roof structure
- Corrosion resistant material
- Roof void benefits from a closed soffit
- Decorative columns and spandrels
- Rainwater drained internally through columns
- Decorative finial to top of wave roof profile
- Robust balustrade panels to the perimeter
- Guttering
- Base plate fixed to below ground

Materials Used

- Cast aluminium columns and spandrel brackets
- Structural aluminium roof construction
- Extruded aluminium rainwater system
- Galvanised mild steel balustrade panels

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com











1

DI

Bespoke size options This

.

Standard Unit Dimensions:

Bandstands Specification Sheel

Colours/Finishes:



ensions are in millimeters, weights in klograms and capacities in thres, are approximate and do not form any part of the contract. All prices are guide prices only and should be used for estimating purposes only. Broap Limited reserve the right to charge the design, specification or price of any items odd at any time. All prices exclude VAT and deview, Plesses Note All information on this data sheet is subject to orientation (NS, EV) all titude and points, but is sufficient for uses a spenar/point point.

Ascot Bandstand BXMW/ASCOT



Finish Options

- Hot dip galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Fire Resistance

Cladding is fire tested to '1Y' for BS 476

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees* on cladding material(s)
- 10 years' warranty* on material (only)
- 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply


Options

•

- Bespoke size options
- Submerged fixing
- Internal lighting or solar lighting

Diagram

Installation



xap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com







CHAS







2

'n

Standard Unit Dimensions:

Bespoke size options

Colours/Finishes:

White Aluminium

RAL 3020

Only

Anthracite Grey

RAL 9005

Nimbus Grey	Traffic Red	Jet Black
BS 4800 14 C 39	RAL 1023	BS 4800 00 A 05
Holly Green	Traffic Yellow	Goose Grey
RAL 5015	RAL 5013	RAL 9016
Mid Blue	Dark Blue	Traffic White
The colours shown are a guide only. Please check a colour chart to see the actual colour.		
Broxap Limited. Rowhurst Industrial		

