Standard Unit Dimensions:

Lengths & Widths:

8000mm x 4000mm

Bespoke size options

Framework

Colours/Finishes:

RAL 9006

White

RAL 3020

Traffic Red

BAL 1023

Traffic Yellov

RAL 5013

Dark Blue

The colours shown are a guide only.

Please check a colour chart to see the actual colour.

Galva Only

Nimbus Grev

14 C 39

RAL 5015

Mid Blue

Holly Gr

RAL 7016

Anthracite Grey

RAL 9005

Jet Black

BS 4800

00 A 05 Goose Grey

RAL 9016

Traffic White

Steel Canyon **BXTS/ENT/BV**





Product Information

These units can be customized to turn angles and accommodate changes in ground level. This modular unit can either be supplied as a single stand alone canopy or linked together to create a walkway.

Features

•

.

- Standard Unit Size: 8000mm x 4000mm
- White PVC Fabric
- Poles and frames galvanized powder coated option available
- Hot dipped galvanized steel fixings .
 - 100% waterproof fabric
 - 100% UV protection

Materials Used

- Made from heavy-duty S355 steel section
- Hot dipped galvanised to BS EN ISO 1461:2009
- **PVC Waterproof Fabric**

Finish Options (Framework)

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com











1

rpii

Standard Unit Dimensions:

Lengths & Widths: 8000mm x 4000mm

Bespoke size options

Framework **Colours/Finishes:** RAL 9006

White

RAL 3020

Traffic Red

BAL 1023

Traffic Yellov

RAL 5013

Dark Blue

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Galvanised Only

Nimbus Grev

14 C 39

RAL 5015

Mid Blue

Holly Gr

RAL 7016 Anthracite Grey

RAL 9005

Jet Black

BS 4800

00 A 05 Goose Grey

RAL 9016

Traffic White

Steel Canyon **BXTS/ENT/BV**



Design Standards

- All structures are installed to tolerances in NSSS 7TH addition Accuracy in Building, by CRB checked, professional installation teams
- BS EN 1993-1-1:2005 Eurocode 3 Design of steel structures
- BS EN 1991-1-3:2003 Eurocode 1 Snow Loads

Fire Resistance

Fabric conforms to Euro class EN13501-1

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings •
 - 10 years' warranty* Ferrari 832
- 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply


Options

- Post protectors
- Framework powder coated to any standard RAL colour
- Central wall


Diagram

Installation

Bolt Cluster **Cone Anchors**







Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com











