Standard Unit Dimensions:

Lengths & Widths:

36000mm x 4800mm

Bespoke size otions available

Framework

Colours/Finishes:

RAL 9006

White

Aluminium

RAL 3020

Traffic Red

RAL 1023

RAL 5013

Dark Blue

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Galvanised

Only

Nimbus Gre

Mid Blue

RAL 7016

Anthracite

Grey

RAL 9005

Jet Black

BS 4800 00 A 05

Goose Grey

RAL 9016

Traffic White

Inverted Conic BXTS/INV/CON





Product Information

The unsuual Inverted Conic can either be coupled up to the main surface water drainage or water can be diverted out of the leg and onto the ground surface to find its way into the drainage system. Inverted conic canopy, white fabric as standard.

Features

.

.

- Poles and frames galvanized
- Framework can be powder coated to a standard colour
- Hot dipped galvanized steel fixings
- 100% waterproof fabric
- 100% UV protection

Materials Used

- Made from heavy-duty S355 steel section
- Hot dipped galvanised to BS EN ISO 1461:2009
- PVC Waterproof Fabric

Finish Options (Framework)

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com











1

1011

Inverted Conic **BXTS/INV/CON**



Design Standards

- All structures are installed to tolerances in NSSS 7TH addition Accuracy in Building, by CRB checked, professional installation teams
- BS EN 1993-1-1:2005 Eurocode 3 Design of steel structures
- BS EN 1991-1-3:2003 Eurocode 1 Snow Loads

Fire Resistance

Fabric conforms to Euro class EN13501-1

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings •
- 10 years' warranty* Ferrari 832
- 12 months' warranty* on parts & labour

4720m

2000

lo,

*Maintenance and other qualifying criteria apply


Options

- Post protectors
- Bespoke sizes available
- Full installation service

Diagram

Installation

Bolt Cluster **Cone Anchors**



Framework **Colours/Finishes:** RAL 9006 RAL 7016 Anthracite Aluminium Grev RAL 3020 RAL 9005 Jet Black BS 4800 00 A 05



White

Galvanised

Only

Standard Unit Dimensions:

Lengths & Widths: 36000mm x 4800mm

Bespoke size otions available

The colours shown are a guide only. Please check a colour chart to see the actual colour.

















2