Anti-Vandal Wardale Cycle Shelter BXMW/AV-WAR-SHELTER





Standard Unit Dimensions:

Length: 4100mm Width: 2140mm Height: 2150mm

Length with Capacities:

4100mm (10 Cycles) 5000mm (12 Cycles)

Other sizes available POA

Colours/Finishes:



Nimbus Grey Traffic Red Jet E

 3S 4800
 14 C 39
 BS 4800
 00 A 05

 Iolly Green
 Traffic Yellow
 Goose Grey

RAL 5015 RAL 5013 RAL 9016

Mid Blue Dark Blue Traffic White

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Product Information

The Anti-Vandal Wardale® cycle shelter is a robust version of our popular and best-selling Wardale. With its modular design the Anti-Vandal Wardale cycle shelter can be linked together to create banks of shelters which allow to you accommodate almost any quantity of cycles. The Anti-Vandal Wardale cycle shelter includes a sliding gate and mechanical code locks for extra security.

Features

- Trapezoidal Metal Profile roof cladding
- 5mm PETg UV Side Panels complete with 5mm mesh
- Robust modular construction
- Adjustable baseplates
- Hot dipped galvanized to BS EN ISO 1461:2009 and Powder Coated
- Mechanical Code Locks
- Space Saving Sliding Gate

Materials Used

- Framework Mild Steel
- Cladding 4 mm PETG uv
- Fasteners Zinc Plated
- · Cover Strips Pre-galvanized steel flat

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com















Anti-Vandal Wardale Cycle Shelter **BXMW/AV-WAR-SHELTER**



Finish Options

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Fire Resistance

Cladding is fire tested to '1Y' for BS 476

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees* on cladding material(s)
- 10 years' warranty* on material (only)
- 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply

Standard Unit Dimensions:


Length: 4100mm Width: 2140mm Height: 2150mm

Length with Capacities:

4100mm (10 Cycles) 5000mm (12 Cycles)

Other sizes available POA

Colours/Finishes:




Please check a colour chart to see the actual colour.


Options

- 5mm PETg UV Roof Panels complete with 5mm mesh
- 6mm polycarbonate for roof and sides complete with 5mm mesh
- Opal Cladding to Roof and Sides
- Extended adjustable baseplates for submerged fixing
- Swinging Security Gates
- Further anti crawl bars can be fitted dependent on surface level
- **Helmet Lockers**
- LED or solar lighting
- Full Installation Service

Diagram



Installation



Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com













