Standard Unit Dimensions:

Bespoke sizes available

Colours/Finishes:

RAL 9006

White Aluminium

RAL 3020

Traffic Red

RAL 1023

Traffic Yellov

RAL 5013

Dark Blue

The colours shown are a guide only. Please check a colour chart to see the actual colour.

Only

s Gre

14 C 39

Holly Green

Mid Blue

RAL 7016

Anthracite

Grey

RAL 9005

Jet Black

BS 4800

00 A 05

Goose Grev

RAL 9016

Traffic White

Baskeyfield Entrance Canopy BXMW/BASKEY





Product Information

This simple, modern entrance canopy comprises mild steel framework along with toughened glass supported on patent aluminium glazing bars. This modern entrance canopy features; 10mm Toughened Glass, Wall Mounted, Patent Aluminium Glazing Bars.

Features

- 10mm Toughened Glass
- Wall Mounted
- Patent Aluminium Glazing Bars
- May Require Existing Steelwork in Building to Achieve Structured Stability (Subject to Canopy Projection and Building Construction)
- Hot dipped galvanized to BS EN ISO 1461:2009

Materials Used

- Framework Mild steel
- Cladding 10mm thick Heat-soaked toughened glass
- Fasteners Zinc plated
- Cover Strips Aluminium capex

Finish Options (Framework)

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com











1

DI

Baskeyfield Entrance Canopy BXMW/BASKEY



Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Fire Resistance

Cladding is fire tested to '1Y' for BS 476

Guarantees, Warranties, Design-Life and Life-Expectancies

- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees* on cladding material(s)
- 10 years' warranty* on material (only)
- 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply


Options

- Heat Soaked and/or Laminated Glass
- Opal or Tinted Glass Cladding
- Powder Coating to a Wide Range of Colours
- Aluminium Profile Weather Resistant Barriers
- Full Installation Service

Diagram



Standard Unit Dimensions:



Please note: these details are specific to a bespoke project and are subject to change according to the requirements of each individual order.

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com







2

'DII

re in millimeters, weights in kilograms and capacities in litres, are approximate and do not form any part of the contract. All prices are guide prices only and should be used for estimating purposes only. Broxap Limited reserve the right to change the design, specification or price of any item sold at any time. All prices execlude VAT and delivery. Please Note: All information on this data sheet is subject to orientation (NS,EW) altitude and proximity to buildings, but is sufficient for use as general/preliminary information).