

## Apollo Junior Cycle Shelter BXMW/APJ



### Standard Unit Dimensions:

Length: 4120mm  
Width (Overall): 2753mm  
Height (Front): 2194mm  
Height (Rear): 1513mm

### Length with Capacities:

3600mm (8 Cycles)  
4100mm (10 Cycles)  
5000mm (12 Cycles)

### Colours/Finishes:

Galvanised Only	White Aluminium	Anthracite Grey
Nimbus Grey	Traffic Red	Jet Black
Holly Green	Traffic Yellow	Goose Grey
Mid Blue	Dark Blue	Traffic White

The colours shown are a guide only.  
Please check a colour chart to see the actual colour.

## Product Information

The Apollo Junior cycle shelter is based on our Apollo design, comprised tubular curved end frames and a curved roof to give a sleek minimalistic design. The Apollo Junior is single access shelter due to the height with cyclists encouraged to enter from the front. Modular in design, the Apollo Junior can also be linked together to create banks of shelters which allow to you accommodate almost any quantity of cycles.

## Features

- Robust modular construction featuring tubular end frames
- Heavy-duty circular uprights and box section purlins and trimmers, assembled with anti-tamper high strength bolts
- Anti-climb end frames
- Surface mounted baseplates
- Hot dipped galvanized to BS EN ISO 1461:2009
- 5mm ClearView PETg UV roof cladding
- Bream Compliant Configurations

## Materials Used

- Framework - Mild Steel
- Cladding - 4 mm PETG uv
- Fasteners - Zinc Plated
- Cover Strips - Pre-galvanized steel flat

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com



## Apollo Junior Cycle Shelter BXMW/APJ

### Finish Options

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

### Weather Resistance

Cladding is UV Stabilised  
Wind resistant to 23m/s

### Fire Resistance

Cladding is fire tested to EN ISO 11925-2

### Guarantees, Warranties, Design-Life and Life-Expectancies


- 25 year structural guarantee\*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 10 years' manufacturers guarantees\* on cladding material(s)
- 10 years' warranty\* on material (only)
- 12 months' warranty\* on parts & labour

\*Maintenance and other qualifying criteria apply


### Options

- Steel Profile, Trapezoidal Roof Cladding
- Opal Roof Cladding
- Submerged Baseplates
- Powder Coating to a wide range of colours
- LED or solar lighting
- Full Installation Service

### Diagram



### Installation



#### Standard Unit Dimensions:

Length: 4120mm  
Width (Overall): 2753mm  
Height (Front): 2194mm  
Height (Rear): 1513mm

#### Length with Capacities:

3600mm (8 Cycles)  
4100mm (10 Cycles)  
5000mm (12 Cycles)

#### Colours/Finishes:

Galvanised Only	RAL 9006 White Aluminium	RAL 7016 Anthracite Grey
BS 4800 10 A 07 Nimbus Grey	RAL 3020 Traffic Red	RAL 9005 Jet Black
BS 4800 14 C 39 Holly Green	RAL 1023 Traffic Yellow	BS 4800 00 A 05 Goose Grey
RAL 5015 Mid Blue	RAL 5013 Dark Blue	RAL 9016 Traffic White

The colours shown are a guide only.  
Please check a colour chart to see the actual colour.

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com

