





Standard Unit Dimensions:

Lengths & Widths: 3000mm x 3000mm 4000mm x 4000mm 5000mm x 5000mm 6000mm x 6000mm 7000mm x 7000mm 8000mm x 8000mm

Framework Colours/Finishes:

	RAL 9006	RAL 7016
Galvanised Only	White Aluminium	Anthracite Grey
BS 4800 10 A 07	RAL 3020	RAL 9005
Nimbus Grey	Traffic Red	Jet Black
BS 4800 14 C 39	RAL 1023	BS 4800 00 A 05
Holly Green	Traffic Yellow	Goose Grey
RAL 5015	RAL 5013	RAL 9016
Mid Blue	Dark Blue	Traffic White
The colours shown are a guide only. Please check a colour chart to see the actual colour.		

Product Information

The white Tornado tensile canopy is a waterproof tensile structure that come in a wide range of sizes and four shape styles. The Linear style can be conjoined to increase the area coverage.

Features

•

- Single column canopy
- 100% waterproof fabric
- 100% UV protection
- Range of standard sizes available

Materials Used

- Made from heavy-duty S355 steel section
- Hot dipped galvanised to BS EN ISO 1461:2009

Finish Options

- Galvanised to BS EN ISO 1461:2009
- Galvanised to BS EN ISO 1461:2009 & Polyester Powder Coated

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com













1

I dimensions are in milimeters, weights in kilograms and capacities in litres, are approximate and do not form any part of the contract. All prices are guide prices only and should be used for estimating purposes only. Broxap Limited reserve the right to change the design, specification or price of any item sold at any time. All prices exclude VAT and delivery. Please Note: All information on this data sheet is subject to orientation (N,S,E,W) altitude and proximity to buildings, but is sufficient for use as general/preliminary information).

Standard Unit Dimensions:

Lengths & Widths: 3000mm x 3000mm 4000mm x 4000mm 5000mm x 5000mm 6000mm x 6000mm 7000mm x 7000mm 8000mm x 8000mm

Framework Colours/Finishes:



Tornado BXTS/PAR/L



Weather Resistance

Cladding is UV Stabilised Wind resistant to 23m/s

Fire Resistance

Cladding is fire tested to '1Y' for BS 476 Fabric conforms to Euro class EN13501-1

Guarantees, Warranties, Design-Life and Life-Expectancies


- 25 year structural guarantee*
- 34 year (min) life expectancy for Hot Dip Galvanizing
- 8-10 year life expectancy on standard powder coatings
- 10-15 year life expectancy on Duplex (Zinc Coated) powder coatings
- 5 years' warranty* Ferrari 832
 - 10 years' warranty* on material (only)
 - 12 months' warranty* on parts & labour

*Maintenance and other qualifying criteria apply

Options


- Framework powder coated to any standard RAL colour
- Post protector Pads
- Aluminium or plastic guttering
- Modular extension to any length
- Internal lighting or solar lighting
- Full installation service
- Bespoke versions available on request

Diagram



Installation

Submerged Baseplate



BREEAM

Broxap Limited, Rowhurst Industrial Estate, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD T: 01782 564411 E: info@broxap.com W: www.broxap.com

ctionline

Constr

SPA





All dimensions are in millimeters, weights in kilograms and capacities in litres, are approximate and do not form any part of the contract. All prices are guide prices only and should be used for estimating purposes only. Broxap Limited reserve the right to change the design, specification or price of any item sold at any time. All prices exclude VAT and delivery. Please Note: All information on this data sheet is subject to orientation (NS,EW) altitude and proximity to buildings, but it sufficient for use as general/preliminary information).

2

- Achilles -

L Member

CE